

IN THE CLAIMS:

All claims are included for the convenience of the Examiner.

1. (Previously Presented) A system, comprising:
a first device capable of generating heat, wherein the first device is to be cooled using a cooling system having an active cooling component in parallel with a passive cooling component, wherein both the active cooling component and the passive cooling component are capable of cooling the first device at the same time.
2. (Original) The system of claim 1, wherein the active cooling component includes a liquid coolant and a pump or a compressor to enhance flow of the liquid coolant.
3. (Original) The system of claim 2, wherein the liquid coolant is to extract heat generated by the first device.
4. (Original) The system of claim 3, wherein the liquid coolant includes one of water, alcohol, glycol, an inert liquid, and a mixture thereof.
5. (Original) The system of claim 4, wherein the active cooling component includes single-phase or two-phase cooling.
6. (Previously Presented) The system of claim 3, wherein the active cooling component includes liquid metal cooling.
7. (Previously Canceled)
8. (Original) The system of claim 3, wherein the active cooling component further includes a heat exchanger to cool the liquid coolant and a pipe loop to transport the liquid coolant.

9. (Original) The system of claim 8, wherein the heat exchanger is a remote heat exchanger (RHE).

10. (Original) The system of claim 9, wherein the passive cooling component includes a first heat pipe having an evaporation end and a condensation end.

11. (Original) The system of claim 10, wherein the evaporation end of the first heat pipe is coupled to the first device, and wherein the condensation end of the first heat pipe is coupled to the heat exchanger.

12. (Original) The system of claim 11, further comprising a second device capable of generating heat, wherein the second device is to be cooled using a second heat pipe.

13. (Original) The system of claim 12, wherein an evaporation end of the second heat pipe is coupled to the second device, and wherein a condensation end of the second heat pipe is coupled to the heat exchanger.

14. (Previously Presented) A method, comprising:
cooling a first device using both active loop cooling and heat pipe cooling,
wherein said active loop cooling includes a flow-enhancing device to enhance
flow of a liquid coolant between the first device and a heat exchanger, wherein
said heat pipe cooling includes a first heat pipe, and wherein a condensation end
of the first heat pipe is directly coupled to the heat exchanger.

15. (Original) The method of claim 14, wherein the flow-enhancing device is a pump or a compressor.

16. (Original) The method of claim 15, wherein the active loop cooling includes single-phase or two-phase cooling, and wherein the liquid coolant includes one of water, alcohol, glycol, an inert liquid, or a mixture thereof.

17-18. (Previously Canceled)

19. (Previously Presented) The method of claim 15, further comprising:
cooling a second device using [said heat pipe cooling, wherein said heat pipe cooling includes] a second heat pipe, and wherein the heat exchanger is used to enable condensation for the second heat pipe.

20. (Previously Presented) An apparatus, comprising:
a first cooling component to provide active cooling to a first heat generating device, the first cooling component including a pipe loop, a flow-enhancer device and a heat exchanger, the pipe loop directly coupled to the first heat generating device; and
a second cooling component to provide passive cooling to the first heat generating device, the second cooling component including a heat pipe coupled to the first heat generating device and to the heat exchanger, wherein both the first cooling component and the second cooling component are capable of operating at the same time.

21. (Original) The apparatus of claim 20, wherein the first cooling component further includes a liquid coolant transported by the pipe loop between the first heat generating device and the heat exchanger, wherein flow of the liquid coolant is enhanced by the flow-enhancer device.

22. (Original) The apparatus of claim 21, wherein the flow-enhancer device is a pump or a compressor.

23-24. (Previously Canceled)

25. (Original) The apparatus of claim 22, wherein the liquid coolant includes one of water, alcohol, glycol, an inert liquid, and a mixture thereof.